

SanPly-4

FLEXIBLE WOOD VENEER

DATA SHEET

SanPly-4® is similar to SanPly-3® with some important additional features. A fourth layer of foil is added which makes SanPly-4 extremely flexible permitting application to tight radii and curved surfaces while also adding significantly to overall stability - it will not crack or split. The four-layer composition eliminates most of the problems frequently encountered with ordinary wood veneer including bubbling and lifting. SanPly-4 is pre-sanded to 280 grit and comes in oversized sheets for simplified lay-up.

SanPly-4 Veneers offer the following benefits:

- All Architectural faces.
- The only Fire Rated sheet veneer in the industry; Class “A” on Prefinished SanPly-4 and Class “B” on unfinished SanPly-4 Veneer sheets.
- Maximum radius ability in the industry with a ¼” end grain bending ability and 90° on a side grain bend.
- Standard sheet sizes are 4’ x 8’ and 4’ x 10”.
- All sheets are sequenced to each other from the same flitch.
- All sheets are pre-sanded to 280 grit.
- Excellent for profile wrapping, hot pressing or cold pressing.
- All sheets are over sized in both directions.
- Tight bending ability with ¼” end grain and 90° side grain ability.
- Better expansion and contraction factors than other paperbacked veneer sheets.
- Over 60 Domestic and Exotic species to choose from.